

FLOODPLAIN MANAGEMENT RESOLUTION

DIVISION 1000. STATUTORY AUTHORIZATION, FINDINGS OF FACT, PURPOSE AND METHODS

SECTION 1010. STATUTORY AUTHORIZATION

Pursuant to Wyoming Statute §18-5-201, in order to promote the public health, safety, morals and general welfare of the county, the Teton County Board of County Commissioners is empowered to regulate and restrict the location and use of buildings and structures and the use, condition of use or occupancy of lands for residence, recreation, agriculture, industry, commerce, public use and other purposes in the unincorporated areas of Teton County. Therefore the Board of County Commissioners of Teton County, Wyoming does ordain as follows:

SECTION 1020. FINDINGS OF FACT

- A. The flood hazard areas of Teton County are subject to periodic inundation, which results in loss of life and property, health and safety hazards, disruption of commerce and governmental services, and extraordinary public expenditures for flood protection and relief, all of which adversely affect the public health, safety and general welfare.
- B. These flood losses are created by the cumulative effect of obstructions in floodplains which cause an increase in flood heights and velocities, and by the occupancy of flood hazards areas by uses vulnerable to floods and hazardous to other lands because they are inadequately elevated, flood proofed or otherwise protected from flood damage.

SECTION 1030. STATEMENT OF PURPOSE

It is the purpose of this resolution to promote the public health, safety and general welfare and to minimize public and private losses due to flood conditions in specific areas by provisions designed to:

- A. Protect human life and health;
- B. Minimize expenditure of public money for costly flood control projects;
- C. Minimize the need for rescue and relief efforts associated with flooding and generally undertaken at the expense of the general public;
- D. Minimize prolonged business interruptions;
- E. Minimize damage to public facilities and utilities such as water and gas mains, electric, telephone and sewer lines, streets and bridges located in floodplains;
- F. Help maintain a stable tax base by providing for the sound use and development of flood-prone areas in such a manner as to minimize future flood blight areas;
- G. Insure that potential buyers are notified that property is in a flood area; and
- H. Ensure that those who occupy the areas of special flood hazards assume responsibility for their actions.

SECTION 1040. METHODS OF REDUCING FLOOD LOSSES

In order to accomplish its purposes, this resolution uses the following methods:

- A. Restrict or prohibit uses that are dangerous to health, safety or property in times of flood, or cause excessive increases in flood heights or velocities.
- B. Require that uses vulnerable to floods, including facilities which serve such uses, be protected against flood damage at the time of initial construction.
- C. Control the alteration of natural floodplains, stream channels, and natural protective barriers, which are involved in the accommodation of floodwaters.
- D. Control filling, grading, dredging and other development which may increase flood damage.
- E. Prevent or regulate the construction of flood barriers which will unnaturally divert floodwaters or which may increase flood hazards to other lands.

DIVISION 1100. DEFINITIONS

Unless specifically defined below, words or phrases used in this resolution shall be interpreted to give them the meaning they have in common usage and to give this resolution its most reasonable application.

Appeal – means a request for a review of the County Engineer’s interpretation of any provisions of this resolution or a request for a variance.

Area of Shallow Flooding – means a designated AO, AH, or VO zone on a community's Flood Insurance Rate Map (FIRM) with a one percent chance or greater annual chance of flooding to an average depth of one to three feet where a clearly defined channel does not exist, where the path of flooding is unpredictable and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow.

Area of Special Flood Hazard – means the land in the floodplain within Teton County subject to a one percent (1%) or greater chance of flooding in any given year. The area may be designated as Zone A on the Flood Hazard Boundary Map (FHBM). After detailed ratemaking has been completed in preparation for publication of the FIRM, Zone A usually is refined into Zones A, AE, AH, AO, AI-99, VO, VI-30, YE or V.

Base Flood – means the flood having a one percent chance of being equaled or exceeded in any given year.

Basement – means any area of the building having its floor sub-grade (below ground level) on all sides.

Crawlspace – see Basement.

Critical Feature – means an integral and readily identifiable part of a flood protection system, without which the flood protection provided by the entire system would be compromised.

Development – means any man-made change in improved and unimproved real estate, including but not limited to buildings or other structures, mining, dredging, filling, grading, paving, excavation or drilling operations or storage of equipment or materials.

Elevated Building – means for insurance purposes, a non-basement building which has its lowest floor raised above ground level by foundation walls, shear walls, posts, piers, pilings or columns.

Existing Construction – means for the purposes of determining rates, structures for which the "start of construction" commenced before the effective date of the FIRM or before May 4, 1989, for FIRMs effective before that date. "Existing construction" may also be referred to as "existing structures."

Existing Manufactured Home Park or Subdivision – means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including, at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed before May 4, 1989, the effective date of the floodplain management regulations adopted by a community.

Expansion to an Existing Manufactured Home Park or Subdivision – means the preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads).

Flood or Flooding – means a general and temporary condition of partial or complete inundation of normally dry land areas from:

- A. The overflow of inland or tidal waters.
- B. The unusual and rapid accumulation or runoff of surface waters from any source.

Flood Insurance Rate Map (FIRM) – means an official map of a community, on which the Federal Emergency Management Agency has delineated both the areas of special flood hazards and the risk premium zones applicable to the community.

Flood Insurance Study – means the official report provided by the Federal Emergency Management Agency. The report contains flood profiles, water surface elevation of the base flood, as well as the Flood Boundary-Floodway Map.

Floodplain or Flood-prone Area – means any land area susceptible to being inundated by water from any source (see definition of flooding).

Floodplain Management – means the operation of an overall program of corrective and preventive measures for reducing flood damage, including but not limited to emergency preparedness plans, flood control works and floodplain management regulations.

Floodplain Management Regulations – means zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances (such as a floodplain ordinance, grading ordinance and erosion control ordinance) and other applications of police power. The term describes such state or local regulations, in any combination thereof, which provide standards for the purpose of flood damage prevention and reduction.

Flood Protection System – means those physical structural works for which funds have been authorized, appropriated, and expended and which have been constructed specifically to modify flooding in order to reduce the extent of the areas within a community subject to a "special flood hazard" and the extent of the depths of associated flooding. Such a system typically includes hurricane tidal barriers, dams, reservoirs, levees or dikes. These specialized flood modifying works are those constructed in conformance with sound engineering standards.

Flood Proofing – means any combination of structural and non-structural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures and their contents.

Floodway (Regulatory Floodway) – means the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than one (1) foot above base flood elevation.

Functionally Dependent Use – means a use which cannot perform its intended purpose unless it is located or carried out in close proximity to water. The term includes only docking facilities, port facilities that are necessary for the loading and unloading of cargo or passengers, and ship building and ship repair facilities, but does not include long-term storage or related manufacturing facilities.

Highest Adjacent Grade – means the highest natural elevation of the ground surface prior to construction next to the proposed walls of a structure.

Historic Structure – means any structure that is:

- A. Listed individually in the National Register of Historic Places (a listing maintained by the Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
- B. Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or a district preliminarily determined by the Secretary to qualify as a registered historic district;
- C. Individually listed on a state inventory of historic places in states with historic preservation programs which have been approved by the Secretary of Interior; or
- D. Individually listed on a local inventory of historic places in communities with historic preservation programs that have been certified either:
 1. By an approved state program as determined by the Secretary of the Interior, or
 2. Directly by the Secretary of the Interior in states without approved programs.

Levee – means a man-made structure, usually an earthen embankment, designed and constructed in accordance with sound engineering practices to contain, control, or divert the flow of water so as to provide protection from temporary flooding.

Levee System – means a flood protection system which consists of a levee, or levees, and associated structures, such as closure and drainage devices, which are constructed and operated in accordance with sound engineering practices.

Lowest Floor – means the lowest floor of the lowest enclosed area (including basement). An unfinished

or flood resistant enclosure, usable solely for parking or vehicles, building access or storage in an area other than a basement area is not considered a building's lowest floor; **provided** that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirement of 44 CFR, Chapter 1, Section 60.3 of the National Flood Insurance Program regulations.

Manufactured Home – means a structure transportable in one or more sections, which is built on a permanent chassis and is designed for use with or without a permanent foundation when connected to the required utilities. The term "manufactured home" does not include a "recreational vehicle".

Manufactured Home Park or Subdivision – means a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.

Mean Sea Level – means, for purposes of the National Flood Insurance Program, the North American Vertical Datum of 1988 or other datum, to which base flood elevations shown on a community's Flood Insurance Rate Map are referenced.

Mobile Home – see Manufactured Home.

New Construction – means, for the purpose of determining insurance rates, structures for which the "start of construction" commenced on or after the effective date of an initial FIRM or after December 31, 1974, whichever is later, and includes any subsequent improvements to such structures. For floodplain management purposes, "new construction" means structures for which the "start of construction" commenced on or after the effective date of a floodplain management regulation adopted by a community and includes any subsequent improvements to such structures.

New Manufactured Home Park or Subdivision – means a manufactured home park or subdivision for which the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including at a minimum, the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads) is completed on or after the effective date of floodplain management regulations adopted by a community.

Recreational Vehicle – means a vehicle which is:

- A. Built on a single chassis;
- B. 400 square feet or less when measured at the largest horizontal projections;
- C. Designed to be self-propelled or permanently towable by a light duty truck; and
- D. Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.

Start of Construction – means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition, placement, or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for basement, footings, piers or foundations or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction

means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.

Structure – means a walled and roofed building, including a gas or liquid storage tank that is principally above ground, as well as a manufactured home.

Substantial Damage – means damage of any origin sustained by a structure whereby the cost of restoring the structure to its before damaged condition would equal or exceed 50 percent of the market value of the structure before the damage occurred.

Substantial Improvement – means any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent of the market value of the structure before "start of construction" of the improvement. This includes structures, which have incurred "substantial damage", regardless of the actual repair work performed. The term does not, however, include either:

- A. Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary conditions; or
- B. Any alteration of a "historic structure", provided that the alteration will not preclude the structure's continued designation as a "historic structure."

Variance – means a grant of relief to a person from the requirement of this resolution, when specific enforcement would result in unnecessary hardship. A variance, therefore, permits construction or development in a manner otherwise prohibited by this resolution. (For full requirements see Section 60.6 of the National Flood Insurance Program regulations.)

Violation – means the failure of a structure or other development to be fully compliant with the community's floodplain management regulations. A structure or other development without the elevation certificate, other certifications, or other evidence of compliance required in 44 CFR, Chapter 1, Section 60.3(b)(5), (c)(4), (c)(10), or (d)(3) of the National Flood Insurance Program regulations is presumed to be in violation until such time as that documentation is provided.

Water Surface Elevation – means the height, in relation to the National Geodetic Vertical Datum (NGVD) of 1929 (or other datum, where specified), of floods of various magnitudes and frequencies in the floodplains of riverine areas.

DIVISION 1200. GENERAL PROVISIONS

SECTION 1220. BASIS FOR ESTABLISHING THE AREAS OF SPECIAL FLOOD HAZARD

The Areas of Special Flood Hazard under Section 1100 are those areas identified by the Federal Emergency Management Agency (FEMA) in a scientific and engineering report entitled, "The Flood Insurance Study for Teton County and Incorporated Areas", dated September 16, 2015, with accompanying Flood Insurance Rate Maps (FIRMS), as published in the Federal Register. Any revisions thereto, shall be reviewed, and either approved, approved with conditions, or disapproved, by the Planning Commission and Board of County Commissioners according to the procedures outlined in Wyo. Stat. §§ 18-5-202(b) and (c) for the preparation and amendment of zoning regulations. The aforesaid Flood Insurance Studies and Flood Insurance Rate Maps are on file at the Office of the County Engineer Department in the Engineering Building located at 320 S. King Street, Jackson, Wyoming.

SECTION 1230. ESTABLISHMENT OF DEVELOPMENT PERMIT

A Development Permit shall be required to ensure conformance with the provisions of this resolution.

SECTION 1240. COMPLIANCE

No structure shall hereafter be located or any structure or land use be altered, or have its use changed without full compliance with the terms of this resolution and other applicable regulations.

SECTION 1250. ABROGATION AND GREATER RESTRICTIONS

This resolution is not intended to repeal, abrogate, or impair any existing easements, covenants, or deed restrictions. However, where this resolution and another regulation, easement, covenant, or deed restriction conflict or overlap, whichever imposes the more stringent restrictions shall prevail.

SECTION 1260. INTERPRETATION

In the interpretation and application of this resolution, all provisions shall be:

- A. Considered as minimum requirements;
- B. Liberally construed in favor of the governing body; and
- C. Deemed neither to limit nor repeal any other powers granted under State Statutes.

SECTION 1270. WARNING AND DISCLAIMER OR LIABILITY

The degree of flood protection required by this resolution is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. On rare occasions greater floods can and will occur and flood heights may be increased by man-made or natural causes. This resolution does not imply that land outside the areas of special flood hazards or uses permitted within such areas will be free from flooding or flood damages. This resolution shall not create liability on the part of the community or any official or employee thereof for any flood damages that result from reliance on this resolution or any administrative decision lawfully made hereunder.

DIVISION 1300. ADMINISTRATION

SECTION 1310. DESIGNATION OF THE FLOODPLAIN ADMINISTRATOR

The County Engineer is hereby appointed the Floodplain Administrator to administer and implement the provisions of this resolution and other appropriate sections of 44 CFR (National Flood Insurance Program Regulations) pertaining to floodplain management. The County Engineer may designate a qualified designee to act as the Floodplain Administrator.

SECTION 1320. DUTIES & RESPONSIBILITIES OF THE FLOODPLAIN ADMINISTRATOR

Duties and responsibilities of the Floodplain Administrator shall include, but not be limited to, the following:

- A. Maintain and hold open for public inspection all records pertaining to the provisions of this resolution.
- B. Review permit application to determine whether a proposed building site, including the placement of manufactured homes, will be reasonably safe from flooding.
- C. Review, approve or deny all applications for development permits required by adoption of this resolution.
- D. Review permits for proposed development to assure that all necessary permits have been obtained from those Federal, State or local governmental agencies (including Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 U.S.C. 1334) from which prior approval is required.
- E. Where interpretation is needed as to the exact location of the boundaries of the areas of special flood hazards (for example, where there appears to be a conflict between a mapped boundary and actual field conditions) the Floodplain Administrator shall make the necessary interpretation. The Floodplain Administrator may request information from the developer to aid in the interpretation.
- F. Notify, in riverine situations, adjacent communities and the State Coordinating Agency, which is Wyoming Office of Homeland Security, prior to any alteration or relocation of a watercourse, and submit evidence of such notification to the Federal Emergency Management Agency.
- G. Assure that the flood carrying capacity within the altered or relocated portion of any watercourse is maintained.
- H. When base flood elevation data has not been provided in accordance with Section 1220, Basis for Establishing the Areas of Special Flood Hazard, of this resolution, the Floodplain Administrator shall review and reasonably utilize any base flood elevation data and floodway data available from a Federal, State or other source, in order to administer the provisions of Division 1400, Provisions for Flood Hazard Reduction, of this resolution. The Floodplain Administrator may require the developer to provide data relating to base flood elevation and floodway data to aid in the administration of Division 1400, Provisions for Flood Hazard Reduction, of this resolution.
- I. When a regulatory floodway has not been designated, the Floodplain Administrator must require that no new construction, substantial improvements, or other development (including fill) shall be permitted within Zones AI-30 and AE on the community's FIRM, unless it is demonstrated that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one foot at any point within the community.
- J. Under the provisions of 44 CFR Chapter 1, Section 65.12, of the National Flood Insurance Program regulations, the Floodplain Administrator may approve certain development in Zones AI- 30, AE, AH, on the community's FIRM which increases the water surface elevation of the base flood by more than one foot, provided that a conditional FIRM revision through FEMA (Conditional Letter of Map Revision) is first obtained.

SECTION 1330. PERMIT PROCEDURES

- A. Application for a Development Permit shall be presented to the Floodplain Administrator on forms furnished by him/her and may include, but not be limited to, plans in duplicate drawn to scale showing the location, dimensions, and elevation of proposed landscape alterations, existing and proposed structures, including the placement of manufactured homes, and the location of the foregoing in relation to areas of special flood hazard. Additionally, the following information is required:
1. Elevation (in relation to mean sea level), of the lowest floor (including basement) of all new and substantially improved structures;
 2. Elevation in relation to mean sea level to which any nonresidential structure shall be floodproofed;
 3. A certificate from a registered professional engineer or architect that the nonresidential floodproofed structure shall meet the floodproofing criteria of Section 1420, Subsection B, Nonresidential Construction of this resolution;
 4. Description of the extent to which any watercourse or natural drainage will be altered or relocated as a result of proposed development; and
 5. Maintain a record of all such information in accordance with Section 1320, Duties and Responsibilities of the Floodplain Administrator, Subsection A, of this resolution.
- B. Approval or denial of a Development Permit by the Floodplain Administrator shall be based on all of the provisions of this resolution and the following relevant factors:
1. The danger to life and property due to flooding or erosion damage.
 2. The susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner.
 3. The danger that materials may be swept onto other lands to the injury of others.
 4. The compatibility of the proposed use with existing and anticipated development.
 5. The safety of access to the property in times of flood for ordinary and emergency vehicles.
 6. The costs of providing governmental services during and after flood conditions including maintenance and repair of streets and bridges, and public utilities and facilities such as sewer, gas, electrical and water systems.
 7. The expected heights, velocity, duration, rate of rise and sediment transport of the floodwaters and the effects of wave action, if applicable, expected at the site.
 8. The necessity to the facility of a waterfront location, where applicable.
 9. The availability of alternative locations, not subject to flooding or erosion damage, for the proposed use.

10. The relationship of the proposed use to the Jackson/Teton County Comprehensive Plan.

SECTION 1340. VARIANCE PROCEDURES

- A. The Board of County Commissioners shall hear and render judgment on requests for variances from the requirements of this resolution.
- B. The Board of County Commissioners shall hear and render judgment on an appeal only when it is alleged there is an error in any requirement, decision, or determination made by the Floodplain Administrator in the enforcement or administration of this resolution.
- C. Any person or persons aggrieved by the decision of the Board of County Commissioners may appeal such decision in the courts of competent jurisdiction.
- D. The Floodplain Administrator shall maintain a record of all actions involving an appeal and shall report variances to the Federal Emergency Management Agency upon request.
- E. Variances may be issued for the reconstruction, rehabilitation or restoration of structures listed on the National Register of Historic Places or the State Inventory of Historic Places, without regard to the procedures set forth in the remainder of this resolution.
- F. Variances may be issued for new construction and substantial improvements to be erected on a lot of one-half acre or less in size contiguous to and surrounded by lots with existing structures constructed below the base flood level, providing the relevant factors in Section 1330, Permit Procedure, Subsection B, of this resolution, have been fully considered. As the lot size increases beyond the one-half acre, the technical justification required for issuing the variance increases.
- G. Upon consideration of the factors noted above and the intent of this resolution, the Board of County Commissioners may attach such conditions to the granting of variances as it deems necessary to further the purpose and objectives of this resolution as set forth in (Section 1030, Statement of Purpose).
- H. Variances shall not be issued within any designated floodway if any increase in flood levels during the base flood discharge would result.
- I. Variances may be issued for the repair or rehabilitation of historic structures upon a determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and the variance is the minimum necessary to preserve the historic character and design of the structure.
- J. Prerequisites for granting variances:
 1. Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.
 2. Variances shall only be issued upon:
 - a. Showing a good and sufficient cause;
 - b. A determination that failure to grant the variance would result in exceptional hardship to the applicant; and

- c. A determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, extraordinary public expense, create nuisances, cause fraud on or victimization of the public, or conflict with existing local laws or resolutions.
 - 3. Any applicant to whom a variance is granted shall be given written notice that the structure will be permitted to be built with the lowest floor elevation below the base flood elevation, and that the cost of flood insurance will be commensurate with the increased risk resulting from the reduced lowest floor elevation.
- K. Variances may be issued for new construction and substantial improvements and for other development necessary for the conduct of a functionally dependent use provided that:
 - 1. The criteria outlined in Section 1340, Variance Procedures, Subsections A. thru I. of this resolution, are met; and
 - 2. The structure or other development is protected by methods that minimize flood damages during the base flood and create no additional threats to public safety.

DIVISION 1400. PROVISIONS FOR FLOOD HAZARD REDUCTION

SECTION 1410. GENERAL STANDARDS

In all areas of special flood hazards the following provisions are required for all new construction and substantial improvements:

- A. All new construction or substantial improvements shall be designed (or modified) and adequately anchored to prevent flotation, collapse or lateral movement of the structure resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy.
- B. All new construction or substantial improvements shall be constructed by methods and practices that minimize flood damage.
- C. All new construction or substantial improvements shall be constructed with materials resistant to flood damage.
- D. All new construction or substantial improvements shall be constructed with electrical, heating, ventilation, plumbing, and air conditioning equipment and other service facilities that are designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding.
- E. All new and replacement water supply systems shall be designed to minimize or eliminate infiltration of floodwaters into the system.
- F. New and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of floodwaters into the system and discharge from the systems into floodwaters.
- G. On-site waste disposal systems shall be located to avoid impairment to them or contamination from them during flooding.

SECTION 1420. SPECIFIC STANDARDS

Development in special flood hazard areas where base flood elevation data has been provided as set forth in Section 1220, Basis for Establishing the Areas of Special Flood Hazard, Section 1320, Duties and Responsibilities of the Floodplain Administrator, Subsection H., or Section 1430, Standards for Subdivision Proposals, Subsection C, of this resolution, shall meet the following standards:

A. **Residential Construction** – new construction and substantial improvement of any residential structure shall have the lowest floor (including basement), elevated one (1) foot above the base flood elevation. Notwithstanding, the interior grade of a below-grade crawlspace may be constructed below an elevation equal to base flood elevation plus one (1) foot provided:

1. That the interior grade of the crawlspace is no lower than two (2) feet below the lowest adjacent grade.
2. The height of the crawlspace measured from the interior grade of the crawlspace to the top of the crawlspace foundation does not exceed four (4) feet at any point.
3. There must be an adequate drainage system that removes floodwaters from the interior of the crawlspace.
4. That the building must be designed and adequately anchored to resist flotation, collapse, and lateral movements of the structure resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy.
5. That the portions of the building below an elevation equal to base flood elevation plus one (1) foot must be constructed with materials resistant to flood damage.
6. That the portions of the building below an elevation equal to the base flood elevation (BFE) plus (1) foot must be constructed by methods and practices that minimize flood damages.
7. That electrical, heating, ventilation, plumbing and air conditioning equipment and other service facilities constructed are designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding.
8. That the areas below the lowest floor that are subject to flooding shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwaters.

A registered professional engineer, architect, or land surveyor shall submit a certification to the Floodplain Administrator that the standards of this subsection as proposed in Section 1330, Permit Procedure, Subsection A.1, of this resolution are satisfied. Floodplain elevations shall be certified by a registered professional engineer or land surveyor.

B. **Nonresidential Construction** – new construction and substantial improvements of any commercial, industrial or other nonresidential structure shall either have the lowest floor (including basement) elevated one (1) foot above the base flood level or together with attendant utility and sanitary facilities, be designed so that below the base flood level the structure is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads and effects of buoyancy. A registered professional engineer or architect shall develop and/or review structural design, specifications, and plans for the construction, and shall certify that the design and methods of construction are in

accordance with accepted standards of practice as outlined in this subsection. A record of such certification, which includes the specific elevation (in relation to mean sea level) to which such structures are floodproofed shall be maintained by the Floodplain Administrator.

C. **Enclosures** – new construction and substantial improvements, with fully enclosed areas below the lowest floor that are usable solely for parking of vehicles, building access or storage in an area other than a basement and which are subject to flooding shall be designed to automatically equalize hydrostatic flood forces on exterior walls by allowing for the entry and exit of floodwaters. Designs for meeting this requirement must either be certified by a registered professional engineer or architect or meet or exceed the following minimum criteria:

1. A minimum of two openings having a total net area of not less than one square inch for every square foot of enclosed area subject to flooding shall be provided.
2. The bottom of all openings shall be no higher than one foot above grade.
3. Openings may be equipped with screens, louvers, valves, or other coverings or devices provided that they permit the automatic entry and exit of floodwaters.

D. **Manufactured Homes**

1. All manufactured homes shall be placed within Zone A as designated on a FIRM shall be installed using methods and practices which minimize flood damage. For the purposes of this requirement, manufactured homes must be elevated and anchored to resist flotation, collapse, or lateral movement. Methods of anchoring may include, but are not limited to, use of over-the-top or frame ties to ground anchors. This requirement is in addition to applicable State and other local anchoring requirements for resisting wind forces.
2. Manufactured homes that are placed or substantially improved within Zones AI-30, AH, and AE as designated on FIRM on sites (i) outside of a manufactured home park or subdivision, (ii) in a new manufactured home park or subdivision, (iii) in an expansion to an existing manufactured home park or subdivision, or (iv) in an existing manufactured home park or subdivision on which a manufactured home has incurred "substantial damage" as a result of a flood, shall be elevated on a permanent foundation such that the lowest floor of the manufactured home is elevated to or above the base flood elevation and be securely anchored to an adequately anchored foundation system to resist flotation, collapse, and lateral movement.
3. Manufactured homes be placed or substantially improved on sites in an existing manufactured home park or subdivision within Zones AI-30, AH and AE as designated FIRM that are not subject to the provisions of paragraph D of this section shall be elevated so that either:
 - a. The lowest floor of the manufactured home is one (1) foot above the base flood elevation; or
 - b. The manufactured home chassis is supported by reinforced piers or other foundation elements of at least equivalent strength that are no less than 36 inches in height above grade and be securely anchored to an adequately anchored foundation system to resist flotation, collapse, and lateral movement.

- E. **Recreational Vehicles** – recreational vehicles placed on sites within Zones AI-30, AH, and AE as designated on the FIRM must either:
1. Be on the site for fewer than 180 consecutive days;
 2. Be fully licensed and ready for highway use; or
 3. Meet the permit requirements of Section 1330, Permit Procedures, Subsection A of this resolution, and the elevation and anchoring requirements for "manufactured homes" in paragraph D of this section. A recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities and security devices, and has no permanently attached additions.

SECTION 1430. STANDARDS FOR SUBDIVISION PROPOSALS

- A. All subdivision proposals including the placement of manufactured home parks and subdivisions shall be consistent with Section 1020, Findings of Fact, Section 1030, Statement of Purpose, and Section 1040, Method of Reducing Flood Losses, of this resolution.
- B. All proposals for the development of subdivisions including the placement of manufactured home parks and subdivisions shall meet Development Permit requirements of Section 1230; Establishment of Development Permit, Section 1330; Permit Procedures, and the provisions of Division 1400, Provisions for Flood Hazard Reduction, of this resolution.
- C. Base flood elevation data shall be generated for subdivision proposals and other proposed development including the placement of manufactured home parks and subdivisions which are greater than 50 lots or 5 acres, whichever is lesser, if not otherwise provided pursuant to Section 1220, Bases for Establishing the Areas of Special Flood Hazard, or Section 1320. Duties and Responsibilities of the Floodplain Administrator, Subsection H., of this resolution.
- D. All subdivision proposals including the placement of manufactured home parks and subdivisions shall have adequate drainage provided to reduce exposure to flood hazards.
- E. All subdivision proposals including the placement of manufactured home parks and subdivisions shall have public utilities and facilities such as sewer, gas, electrical and water systems located and constructed to minimize or eliminate flood damage.

SECTION 1440. STANDARDS FOR AREAS OF SHALLOW FLOODING (AO/AH ZONES)

Located within the areas of special flood hazard established in Section 1220, Basis for Establishing the Areas of Special Flood Hazard, of this resolution, are areas designated as shallow flooding. These areas have special flood hazards associated with base flood depths of 1 to 3 feet where a clearly defined channel does not exist and where the path of flooding is unpredictable and where velocity flow may be evident. Such flooding is characterized by ponding or sheet flow; therefore, the following provisions apply:

- A. All new construction and substantial improvements of **residential** structures have the lowest floor (including basement) elevated above the highest adjacent grade at least as high as the depth number specified in feet on the FIRM (at least two feet if no depth number is specified).
- B. All new construction and substantial improvements of nonresidential structures shall:

1. Have the lowest floor (including basement) elevated above the highest adjacent grade at least as high as the depth number specified in feet on the community's FIRM (at least two feet if no depth number is specified); or
 2. Together with attendant utility and sanitary facilities be designed so that below the base flood level the structure is watertight with walls substantially impermeable to the passage of water and with structural components having the capability of resisting hydrostatic and hydrodynamic loads of effects of buoyancy.
- C. A registered professional engineer, surveyor or architect shall submit a certification to the Floodplain Administrator that the standards of this Section are satisfied.
- D. Within Zones AH or AO adequate drainage paths around structures on slopes, to guide floodwaters around and away from proposed structures shall be provided.

SECTION 1450. FLOODWAYS

Floodways located within areas of special flood hazard established in Section 1220, Bases for Establishing the Areas of Special Flood Hazard, of this resolution, are areas designated as floodways. Since the floodway is an extremely hazardous area due to the velocity of flood waters which carry debris, potential projectiles and erosion potential, development within floodways designated on the FIRM, shall comply with the following standards:

- A. Encroachments are prohibited, including fill, new construction, substantial improvements and other development within the adopted regulatory floodway *unless* it has been demonstrated through hydrologic and hydraulic analyses performed in accordance with standard engineering practice that the proposed encroachment would not result in any increase in flood levels within the community during the occurrence of the base flood discharge.
- B. If Subsection A above is satisfied, all new construction and substantial improvements shall comply with all applicable flood hazard reduction provisions of this Division.
- C. Under the provisions of 44 CFR Chapter 1, Section 65.12, of the National Flood Insurance Regulations, encroachments within the adopted regulatory floodway that would result in an increase in base flood elevations may be permitted, provided that the community **first** obtains a conditional FIRM and floodway revision through FEMA.

SECTION 1460. PENALTIES FOR NONCOMPLIANCE

No person shall locate, erect, construct, reconstruct, enlarge, change, maintain or use any building or any land in violation of this resolution. Each day's continuation of such violation is a separate offense. Whoever violates any of the provisions of this resolution shall be fined not more than seven hundred fifty dollars (\$750.00) for each offense. Additionally, this resolution is enforceable by injunction, mandamus or abatement and nothing herein contained shall prevent Teton County from taking such other lawful action as is necessary to prevent or remedy any such violation. Violations shall be enforced through Wyoming State Statutes 18-5-204 – 207.

SECTION 1470. EFFECTIVE DATE

This resolution was approved by the Board of County Commissioners on August 19, 2010, and is effective upon filing with the Teton County Clerk.